

Designed as reliable, powerful, scalable modular storage systems offering a unified storage architecture—with exceptional value—for large-enterprise data center applications and consolidations



IBM System Storage N7000 series Modular Disk Storage Systems



Highlights

- **Scalable—Designed for nondisruptive expansion to more than 1.1 petabytes (1.1 PB or 1100 TB) storage capacity**
- **Application availability—N7000 systems with Data ONTAP® enable application-level recovery in minutes, not hours, upon failure or user error**
- **Versatile—Integrated architecture designed to support concurrent block I/O and file serving over Ethernet and Fibre Channel SAN infrastructures**
- **Performance—Delivers high, consistent performance for mission-critical applications**
- **Efficient consolidation—Intended to provide storage for multiple applications in a system with FlexShare™ to ensure that critical workloads get priority service**

In an increasingly demanding and competitive business landscape, effective data management is essential to the success of the enterprise. Data availability from any location gives employees, partners, and customers the up-to-the-minute information they need to work productively, make timely decisions, and meet business goals. Information technology professionals facing these challenges are under pressure to deliver more capacity and at higher levels of service. Yet critical resources—staffing, budget, power, cooling, and floor space—are often constrained.

These demands call for enterprise-class storage systems with the flexibility to support changing IT requirements, accommodate continuous data growth, satisfy application-level service requirements, and unify SAN and NAS infrastructures with the expectation of reducing overall costs.

The IBM System Storage™ N7000 series systems are intended to help IT organizations tackle the challenge of effective data management using virtualization technology and a unified storage architecture. The N7000 series is designed to deliver high-end enterprise storage and data management value with midrange affordability. Built-in enterprise serviceability and manageability features help support your efforts to increase reliability, simplify, and unify storage infrastructure and maintenance, and deliver exceptional economy.

The N7000 series, like all N series systems, provides powerful virtualization and thin-provisioning capabilities intended to maximize storage utilization and staff productivity while minimizing the use of power, cooling, and floor space. Staff productivity can be enhanced by an integrated suite of application-aware manageability software that can provide policy-based automation to otherwise manual tasks.

The IBM N7000 series is designed to provide remarkable versatility by unifying FC SAN, iSCSI SAN, NAS, primary, nearline, and regulatory compliance data retention and archival storage in an integrated architecture. The combination of versatility and simplicity of N series systems is intended to help IT professionals respond quickly to changing business needs.

The N7000 series combines the benefits of a unified storage architecture suite of application-aware software with massive scalability, which is intended to provide an ideal platform for large-scale data center applications and storage consolidations.

In addition, the N7000 series ordered through a Gateway feature can help you optimize the use of your existing storage equipment, and improve efficiency and return on investment while continuing to support different access methods for different business solutions throughout the enterprise.

Designed to support scalability, versatility, flexibility, reliability, and availability with outstanding value

Scalability. The N7000 series is designed to meet the massive storage scalability and I/O scalability needs that are critical in large data center environments. The N7900 system can be configured with 1.176 PB of raw storage capacity using up to 1,176 disk drives. The N7700 system can support 840 TB of capacity using as many as 840 disk drives.

Both the N7900 and the N7700 systems offer high-bandwidth controller designs, which can be in an active-active configuration. Each system offers 16 4-Gbps Fibre Channel (FC) ports

and 12 Gigabit Ethernet (GbE) ports standard with the system's 10 PCI-e and six PCI-x expansion slots that can accommodate quad-port 4-Gbps FC adapter cards and 10 GbE adapter cards. For additional connectivity, the N7000 series can expand to a maximum of 56 Fibre Channel ports and 52 Ethernet ports.

Versatility. The unified storage architecture of the N7000 series can help eliminate the need to manage separate NAS and SAN storage by providing concurrent support for block and file protocols via Ethernet and Fibre Channel interfaces. With support for Fibre Channel and SATA hard drives, the N7000 product line also has the flexibility to be used for primary and secondary tiered storage.

Storage provisioning can take hours on other storage systems but with N series system's thin provisioning capabilities provided by FlexVol®, volumes can be expanded and contracted automatically without IT staff intervention or disruption to applications.

Another feature of the N series Data ONTAP operating system, FlexClone®, enables the nearly instant creation of clones without requiring incremental storage. FlexClone can dramatically accelerate test and development cycles for IT projects.

Efficient consolidation. The N7000 series is designed to consolidate and serve data for a wide variety of workloads, including mission-critical business applications, technical applications, databases, e-mail, home directories, digital media, backup and recovery, regulatory compliant data retention, and archival. IBM N series systems support Windows®, UNIX®, including AIX®, Solaris™ and HP-UX, and Linux® host operating systems as well as VMware for server virtualization.

IT organizations can be challenged with poor response times during peak hours of operations after consolidating storage systems with dissimilar data workloads on to a single platform. To help address this challenge, N series offers FlexShare quality-of-service software, which is intended to enable storage administrators to set and dynamically adjust workload priorities. FlexShare can help ensure that important applications get fast response times.

Application availability. N7000 systems combine a variety of features to meet the need for continuous availability. Complementing the high-availability hardware design is the proven reliability of the Data ONTAP operating system and RAID-DP™ (N series implementation of RAID-6), which uniquely provides double-level RAID data protection to help ensure that data is not lost in the event of multiple disk drive failures. In

addition, RAID-DP has negligible performance impact. The N7000 also supports simple yet powerful synchronous, semi-synchronous and asynchronous mirroring that can be deployed in one-to-one, one-to-many and many-to-one mirroring configurations.

The N7000 can serve as the foundation for a comprehensive data management solution consisting of hardware, software, and services. With an appliance architecture, and built-in backup and recovery software, an N7000 solution is designed to address the entire spectrum of data availability challenges while offering value in price/performance and scalability.

Ultimately what matters is application-level availability, and this is where N series systems excel. Snapshot™, a standard feature of Data ONTAP, makes it possible to instantly revert to a previous version of data upon failure or user error. N series Snapshot copies are unique in that they can be created frequently during production because they use only a small amount of incremental storage and have virtually no impact on performance. Host-based SnapManager® software integrates Snapshot management with applications designed to ensure consistent backup images and application-level recovery in minutes.

Performance. High performance and massive storage capacity are characteristics that make the N7000 systems ideal for large-scale applications and storage consolidation. An N7000 system is designed to complete jobs quickly and handle a large number of users via a powerful, high-bandwidth architecture with scalability to 1,176 disk drives capable of delivering up to 1.176 PB of raw storage capacity. With large cache memory configurations, expandable high-performance I/O, 4-Gbps FC SAN support, 4-Gbps disk drive support, and support for 10-Gbps Ethernet, the N7000 delivers exceptional enterprise-class system performance.

N7000 near-line storage capabilities

The N7000 is well suited for near-line storage configurations. An N7000 system populated with Fibre Channel disk drives that backs up to another N series system populated with SATA disk drives offers disk-to-disk backup capabilities that are designed to help you fill the price/performance gap between fast but costly primary storage and less costly but slow archival (tape and optical) storage. Utilizing SATA disk drive technology, you could achieve near-primary storage performance at near-tape storage costs. A disk-based, secondary storage device for enterprise applications, N7000 disk-to-disk environments are designed to complement

and dramatically improve existing tape backup, archiving and data protection schemes. They do so by inserting economical and simple-to-use disk-based storage between application storage and tape libraries in a three-tier storage architecture.

This arrangement is designed to provide economical storage and rapid disk-based access to reference data to help address business and regulatory requirements. It can serve as a key component in an information lifecycle management process by storing less-critical data on a device where cost and performance stand between primary and tape storage.

Combined with SnapVault®, the N7000 disk-to-disk backup environments are designed to serve as a robust and fully integrated appliance that makes backing up and restoring data rapid and reliable. Backing up directly to an N7000 system in a near-line storage configuration, and then to tape can help your organization enhance data protection management, improve primary storage and tape library performance, and reduce backup resource requirements and costs. Two N series systems operating in a disk-to-disk backup scenario are designed to be faster and to consume less application-server CPU processing power than direct backup to

tape. SnapVault software can be used to help reduce network bandwidth consumption by supporting incremental block transfers to backup data across a LAN or WAN. SnapMirror® software, which replicates data at high speeds over a LAN or a WAN, is designed to provide high data availability and fast recovery for mission-critical applications.

IBM N series systems using NearStore® software can use the Advanced Single Instance Storage (A-SIS) software feature for better storage utilization. A-SIS software enables N series systems to deduplicate stored data at the block level in order to conserve physical disk space when making disk-to-disk copies of primary data. Traditionally when copies of volumes are created, every duplicate data string is also copied, resulting in an inefficient use for secondary storage. A-SIS deduplication helps eliminate this inefficiency.

Support for data retention through non-erasable, non-rewriteable security capabilities

The N7000 offers multiple capabilities in the area of data retention. It can serve as a high-performance device for storing mission-critical production data and as a data-retention system by running SnapLock® software. The N7000 with SnapLock software is designed to

deliver high-performance and high-security data permanence to disk-based nearline and primary N series storage. An optional feature of the proven Data ONTAP operating system, SnapLock software supports the accuracy, integrity, and security of data. It helps prevent the alteration of business records and allows data to be rapidly accessible online for long periods of time.

SnapLock offers capabilities to help you address regulatory and best-practices records retention requirements by supporting the creation of non-rewritable, non-erasable volumes on IBM N series systems. This functionality is designed to prevent critical files from being altered or deleted until a specified retention date.

SnapLock is also designed to replicate non-erasable, non-rewriteable data securely and automatically between multiple N series systems using SnapMirror software. The non-erasable, non-rewriteable to non-erasable, non-rewriteable replication of data at remote sites can help your organization address regulatory concerns or best practices, resulting in a highly robust compliant data protection solution. Non-erasable, non-rewriteable data can also be backed up to tape for an additional level of data protection.

Software

Operating system Data ONTAP

Operating systems supported Windows 2000, Windows Server® 2003, Windows XP, Linux, Sun™ Solaris, IBM AIX, HP-UX, Mac OS, VMware ESX

Software features

Standard

Integrated RAID manager, including RAID-DP
Snapshot
Fast Boot
NIS
DNS
FileView®
FlexVol
FlexShare
Disk Sanitization
SecureAdmin™
Network Data Management Protocol (NDMP)

Licensed

CIFS
NFS
HTTP
FTP
iSCSI
FCP
FlexCache™
FlexClone
FlexScale
MultiStore®
Clustered Failover
SnapMirror
SyncMirror®
SnapRestore®
Single Mailbox Recovery
SnapVault
SnapMover®
NearStore
Advanced Single Instance Storage
SnapValidator®
SnapLock
MetroCluster
Manageability Software
Application Suite
SnapManager for Microsoft® Exchange
SnapManager for Microsoft SQL Server®
SnapManager for Microsoft Office SharePoint®
SnapManager for Oracle
SnapManager for SAP
SnapManager for Virtual Infrastructure
Server Suite
SnapDrive®
Virtual File Manager™— Enterprise Edition
Virtual File Manager—Migration Edition
Storage Suite
Protection Manager
Provisioning Manager
File Storage Resource Manager
Operations Manager

Specifications		
	N7700	N7900
Machine Type Model	2866-A21	2867-A21
Gateway Machine Type Model	2866-A21 (w/FC 9551)	2867-A21 (w/FC 9551)
Controller Configuration	Dual (active/active)	Dual (active/active)
Processors Speed and Type	2.6 GHz AMD™ Opteron™	2.6 GHz AMD Dual Core Opteron
Number of Processors	4	8
Random Access memory	32 GB	64 GB
Nonvolatile Memory	1 GB	4 GB
Integrated I/O Ports		
Fibre Channel Ports/Speed	16 (4-Gbps)	16 (4-Gbps)
Ethernet Ports/Speed	12 (1-Gbps)	12 (1-Gbps)
Storage Scalability		
Maximum Number of Fibre Channel Loops	10	14
Maximum Raw Capacity	840 GB	1176 GB
Maximum Number of Disk Drives	840	1176
Maximum Volume Size	16 TB	16 TB
Maximum Number of Volumes/LUNs	2048	2048
Maximum Number of Storage Enclosures	60	84
Disk Expansion Units Supported	EXN4000 - 4-Gbps Fibre Channel Disk Storage Expansion Unit: 4-Gbps Fibre Channel: 300 GB, 10,000, 15,000 rpm ; 450 GB, 15,000 rpm 2-Gbps Fibre Channel: 300 GB, 10,000, 15,000 rpm ; 450 GB, 15,000 rpm EXN1000 - SATA Disk Storage Expansion: SATA: 500 GB, 7,200 rpm; 750 GB, 7,200 rpm, 1 TB	
I/O Scalability		
PCI-Express (PCI-e) Expansion Slots	10	10
PCI-x Expansion Slots	6	6
Maximum number of FC Ports	56	56
Maximum number of Ethernet Ports	52	52



For more information

Contact your IBM representative or IBM Business Partner, or visit:

ibm.com/systems/storage/network

For technical specifications, optional I/O expandability and software features, functions and benefits of the N7000 series, visit:

ibm.com/systems/storage/network/n7000/appliance

For N7000 series interoperability, visit:

ibm.com/systems/storage/network/interophome.html

Additionally, IBM Global Financing can tailor financing solutions to your specific IT needs. For more information on great rates, flexible payment plans and loans, and asset buyback and disposal, visit:

ibm.com/financing

IBM is not responsible for the performance or interoperability of any non-IBM products discussed herein. Performance data for IBM and non-IBM products and services contained in this document was derived under specific operating and environmental conditions. The actual results obtained by any party implementing such products or services will depend on a large number of factors specific to such party's operating environment and may vary significantly. IBM makes no representation that these results can be expected or obtained in any implementation of any such products or services.

MB, GB, TB and PB equal 1,000,000, 1,000,000,000, 1,000,000,000,000 and 1,000,000,000,000,000 bytes, respectively, where referring to storage capacity. Actual storage capacity will vary based upon many factors and may be less than stated. Some numbers given for storage capacities give capacity in native mode followed by capacity using data compression technology.

IBM's customer is responsible for ensuring its own compliance with legal requirements. It is the customer's sole responsibility to obtain advice of competent legal counsel as to the identification and interpretation of any relevant laws and regulatory requirements that may affect the customer's business and any actions the customer may need to take to comply with such laws. IBM does not provide legal advice or represent or warrant that its services or products will ensure that the customer is in compliance with any law.

Max. capacity is derived based on the type, size, and number of the drives. Max. capacity and volume size are calculated using Base10 arithmetic (i.e., 1 TB = 1,000,000,000,000 bytes).

© Copyright IBM Corporation 2009

IBM Systems and Technology Group
Route 100
Somers, NY 10589

Produced in the United States of America
February 2009
All Rights Reserved

IBM, the IBM logo, ibm.com, AIX and System Storage are trademarks or registered trademarks of International Business Machines Corporation in the United States, other countries or both. These and other IBM trademarked terms are marked on their first occurrence in this information with the appropriate symbol (® or ™), indicating US registered or common law trademarks owned by IBM at the time this information was published. Such trademarks may also be registered or common law trademarks in other countries. A current list of IBM trademarks is available on the Web at ibm.com/legal/copytrade.shtml.

Data ONTAP, FilerView, FlexCache, FlexClone, FlexShare, FlexVol, MultiStore, NearStore, RAID-DP, SecureAdmin, SnapDrive, SnapLock, SnapManager, SnapMirror, SnapMover, SnapRestore, Snapshot, SnapValidator, SnapVault, SyncMirror and Virtual File Manager are trademarks or registered trademarks of Network Appliance, Inc., in the U.S. and other countries.

Linux is a registered trademark of Linus Torvalds in the United States, other countries or both.

Microsoft, SharePoint, SQL Server, Windows, Windows Server and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States, other countries or both.

UNIX is a registered trademark of The Open Group in the United States and other countries.

Sun and Solaris are trademarks of Sun Microsystems, Inc. in the United States and other countries.

Other company, product and service names may be trademarks or service marks of others.

This document could include technical inaccuracies or typographical errors. IBM may make changes, improvements or alterations to the products, programs and services described in this document, including termination of such products, programs and services, at any time and without notice. Any statements regarding IBM's future direction and intent are subject to change or withdrawal without notice, and represent goals and objectives only. The information contained in this document is current as of the initial date of publication only and is subject to change without notice. IBM shall have no responsibility to update such information.



Recyclable, please recycle.

TSD02538-USEN-11