

EMC Symmetrix DMX2000

The EMC® Symmetrix® DMX2000 is a double-bay storage system that can be configured with up to 288 2Gb/s high-performance Fibre Channel disk drives providing a maximum raw capacity of over 86 TB. The 24-slot Direct Matrix backplane accommodates configurations of up to eight global memory directors, up to twelve channel I/O directors, and either four or eight dedicated disk I/O directors.

System Throughput

The Symmetrix Direct Matrix Architecture® provides dedicated, non-blocking interconnects between I/O directors and global memory regions. With up to 128 dedicated data paths operating at 500 MB/s, the Direct Matrix delivers virtually unrestricted concurrent I/O throughput. A separate low-latency message matrix supports inter-processor communications between processors for maximum efficiency.

DMX data paths	32-128	8 per I/O Director, 16 per Global Memory Director
DMX data bandwidth	16-64 GB/s	
DMX message bandwidth	3.2-6.4 GB/s	
PowerPC CPUs	20-116	1GHz
Global Memory	4-256 GB	Available in 2, 4, 8, 16 and 32 GB increments
Concurrent Memory transfers	16-32	4 per Global Memory Director

Connectivity

The Symmetrix DMX2000 supports up to twelve (12) high-speed Channel I/O Directors with four SMP-driven pipeline slices each. Optimized hardware logic and data protection encoding ensures end-to-end data integrity with automated channel failover for maximum availability and load balancing.

Symmetrix DMX systems support all popular hardware and operating system platforms, storage area networks (SANs), and high-availability cluster environments.

2Gb/s Fibre Channel host/SAN ports	16-96	8 per Fibre Channel Director
2Gb/s Fibre Channel remote replication ports	2-8	1-4 per Fibre Channel Director
1Gb/s Ethernet iSCSI ports	2-48	1-4 per Multi-protocol Channel Director
1Gb/s Ethernet remote replication ports	2-8	1-4 per Multi-protocol Channel Director
2Gb/s FICON host ports	2-48	1-4 per Multi-protocol Channel Director
ESCON host ports	16-96	8 per ESCON Channel Director
ESCON remote replication ports	2-8	1-4 per ESCON Channel Director

Mixed combinations of the above port types depend upon configuration. Refer to the EMC Support Matrix on EMC.com or contact your local EMC sales representative for specific configuration support.

Disk Drives & Drive Connectivity

The Symmetrix DMX2000 disk drive infrastructure is architected with the latest 2Gb/s dual-ported Fibre Channel disk drives, each supported by two independent disk I/O directors with automatic failover and fault isolation.

	Min Capacity	Max Capacity	
Disk Directors	4	8	8 ports per Director
Disk Channels	32	64	Each drive supported by 2 channels
2GB/s FC Disk Drives	128	288	
Drives per Channel Pair	9	18	

Available Drives:

	73 GB	73 GB	146 GB	300 GB
Capacity	73 GB	73 GB	146 GB	300 GB
Rotational Speed	10,000 rpm	15,000 rpm	10,000 rpm	10,000 rpm
Interface	2Gb/s FC	2Gb/s FC	2Gb/s FC	2Gb/s FC
Internal data rate	475-841 Mb/s	609-891 Mb/s	475-841 Mb/s	475-841 Mb/s
Average access time (read/write)	4.9/5.5 ms	3.8/4.1 ms	4.9/5.5 ms	4.9/5.5 ms
Raw Capacity	73.3 GB	73.3 GB	146.8 GB	300.0 GB
Formatted capacity – open systems	73.10 GB	73.10 GB	146.00 GB	299.32 GB
Formatted capacity – mainframe	72.17 GB	72.17 GB	144.60 GB	295.71 GB
Formatted capacity – iSeries	68.71 GB	68.71 GB	137.42 GB	n/a

Data Protection Options

- RAID 0: Data striped across two to eight hypervolumes
- RAID 1: Mirrored pair of two hypervolumes
- RAID 1/0: Data striped across four mirrored pairs of hypervolumes
- RAID 5: Data striped on four or eight hypervolumes (with rotating parity)
- Parity RAID: Data volumes on three or seven hypervolumes with dedicated parity hypervolume
- Configurable global hot-spare pool

Symmetrix DMX systems can be integral elements of a comprehensive information lifecycle management strategy—a strategy that helps your enterprise attain the maximum value from its information, at the lowest TCO, at every point in the information lifecycle. Information lifecycle management maps the right service level to the right application at the right cost—at the right time.



System Capacities

	73 GB Drives		146 GB Drives		300 GB Drives	
	Min. Capacity (GB)	Max. Capacity (GB)	Min. Capacity (GB)	Max. Capacity (GB)	Min. Capacity (GB)	Max. Capacity (GB)
Number of Disks	128	288	128	288	128	288
Raw Capacity						
Open	9,356	21,052	18,688	42,048	38,312	86,203
Mainframe	9,237	20,784	18,508	41,644	37,850	85,163
Mirrored Capacity						
Open	4,678	10,526	9,344	21,024	19,156	43,101
Mainframe	4,618	10,392	9,254	20,822	18,925	42,581
Parity 3+1 Capacity						
Open	7,017	15,789	14,016	31,536	28,734	64,652
Mainframe	6,928	15,588	13,881	31,233	28,387	63,872
Parity 7+1 Capacity						
Open	8,187	18,421	16,352	36,792	33,523	75,428
Mainframe	8,083	18,186	16,195	36,439	33,119	74,518

Configurations with mixed drive capacities and speeds are allowed depending upon configuration. 12 GB of total capacity will be reserved for internal Symmetrix file system use. All capacities are based on 1 GB = 1,000,000,000 bytes. Actual usable capacity may vary depending upon operating system.

Disk Emulation

DMX2000	Open Systems	3380K	3390-1	3390-2	3390-3	3390-9	3390-27
MB/Volume	30,720	1,891	946	1,892	2,838	8,514	27,845
Bytes/Track	32,768	47,476	56,66 4	56,66 4	56,66 4	56,66 4	56,664
Bytes/Cylinder	491,520	712,140	849,960	849,960	849,960	849,960	849,960
Cylinders/Volume	65,536	2,655	1,113	2,226	3,339	10,017	32,760

Available Software*

The Engenuity™ operating environment delivers the highest levels of performance and systems and data integrity, while providing a foundation for storage applications such as the TimeFinder™ and SRDF® families of local and remote replication.

Platform Software

AutoSwap
 Catalog Solution
 Double Checksum
 InfoMover
 Enterprise Storage Platform (ESP)
 Performance Essential
 ResourcePak for TPF
 ResourcePak for Windows
 SRDF/Synchronous
 SRDF/Asynchronous
 SRDF/Star
 SRDF/Data Mobility
 SRDF/Automated Replication
 SRDF/Consistency Groups
 SRDF/Cluster Enabler for MSCS
 SRDF/Cluster Enabler for VCS
 SRDF/Automated Availability Manager
 SRDF/Host Component
 SRDF/Mode Change
 SRDF/Adaptive Copy
 COMPAV/MA
 Open Replicator for Symmetrix
 ResourcePak Base for OS/390 and z/OS
 ResourcePak Extended for OS/390 and z/OS
 Data Relocation Utility

TimeFinder/Clones
 TimeFinder/Mirror
 TimeFinder/Snap
 TimeFinder/Consistency Groups
 TimeFinder/Exchange Integration Module
 TimeFinder/SQL Integration Module
 VSAM Assist
 TPF Controls for SRDF
 TPF Controls for TimeFinder
 CopyPoint for OS/400
 CopyCross
 EMC Compatible Peer (providing IBM PPRC function)
 EMC Compatible Extended (providing IBM XRC function)

Information Management Software

Replication Manager/Remote (SDMM)
 Replication Manager/Local (ERM)
 EMC Data Manger (EDM)
 EMC Legato Automated Availability Manager

ControlCenter Storage Management Software

Storage Device Management
 Symmetrix Manager
 Symmetrix Optimizer
 SRDF/TimeFinder Manager for OS/400

SRM Monitoring and Reporting
 StorageScope
 StorageScope File Level Reporter
 Workload Analyzer

SRM Planning and Provisioning
 SAN Manager
 SAN Advisor
 Automated Resource Manager

Infrastructure Software
 PowerPath

* Contact your EMC sales representative for software license model numbers, prerequisites, and additional information.

Physical & Cooling Specifications

Height** (in/cm)	Width (in/cm)	Depth (in/cm)	Front Service Area (in/cm)	Rear Service Area (in/cm)	Weight (lb/kg)	Power (kVA)	Cooling (Btu/hr)
75.4/191.5	48.0/121.9	37.5/95.3	36.0/91.4	36.0/91.4	3,154/1,433	9.5	32,785

All dimensions are cabinet/enclosure size without shipping brackets, stabilizers, or sound mufflers. Weight, power, and cooling are maximum for a full configuration.

**An additional 18 in. (45.7 cm) is required for ceiling/top clearance.

Power Specifications

Redundant main and auxiliary power connections
 2 (N+1) power supply redundancy
 Modular power zones with two to six power modules

	North America and International single-phase	North America and International 3-phase (Delta - 4 Wire)	International* 3-phase (Wye - 5 Wire)
Input Voltage (VAC)	200-240	200-240	200-240
Frequency (Hz)	47-63	47-63	47-63
Circuit Breaker (Amps), recommended	60	50	32
Power Drops	4	4	4
Power Connector	(4) 9P63U2T	(4) 9P54U2T	Country Specific
User Connector	(4) 9C63U2T	(4) 9C54U2T	Country Specific

* For higher voltage installations (380-415 VAC line to line) a 32 amp rated breaker is recommended.

Environmental Specifications (operating)

Temperature (°F/°C)	50-90°F/10-32°C
Altitude (ft/m), max.	8,000/2,500
Humidity (%), non-condensing	20-80
Raised Floor	Recommended

www.EMC.com



EMC Corporation
 Hopkinton
 Massachusetts
 01748-9103
 1-508-435-1000
 In North America 1-866-464-7381

EMC², EMC, EMC ControlCenter, Direct Matrix Architecture, PowerPath, ResourcePak, SRDF, Symmetrix, TimeFinder, and where information lives are registered trademarks and Automated Resource Manager, CopyCross, EDM, SAN Advisor, SAN Manager, StorageScope, InfoMover, SDMS, and Symmetrix DMX are trademarks of EMC Corporation. Other trademarks are the property of their respective owners. All specifications are subject to change without prior notice.

© Copyright 2002, 2005 EMC Corporation.
 All rights reserved. Published in the USA. 04/05

Specification Sheet
 C1004.9