

**Specifications**



**DocuTech 6100/6135** deliver high-value digital services like print on demand, distribute then print, and 1:1 marketing. Now, you can start on the road to digital printing success at a pace that's just right—from 96 to 135 pages per minute.

DocuTech 6100/6135 are ideal entry points to enter the digital world, or an economical way to complement your current DocuTech system capacity.

In either case, your business will move faster and more productively when it is...  
**powered by DocuTech.**

# Xerox DocuTech 6100 / 6135





For more information on the Xerox DocuTech 6110/6135 Production Publishers call 13 14 12 or visit us on the Web at: [www.fujixeroc.com.au](http://www.fujixeroc.com.au)

## Xerox DocuTech 6100/6135 Production Publisher Specifications



### Printer Control Module

- Sun Blade 2000
- Dual 900 MHz UltraSparc III processors
- 73 GB system disk
- 2 GB memory
- DVD-ROM Drive
- 17.4 inch colour flat panel display
- Keyboard and mouse
- Ethernet interface (10/100BaseT)
- Image processing printer interface card
- Controller stand

### Printer Module

- Xerographic Engine
- Print speeds:
  - DocuTech 6100: Up to 96 ppm. (A4)
  - DocuTech 6135: Up to 135 ppm. (A4)
- On-site upgrades are available for the DocuTech 6100
- Simplex or duplex printing
- Laser raster output at 600 dpi
- ImageSense Technology
- On-line stitching/binding
- Right and left side stitching/binding
- Optional Interposers:
  - 2 Tray Interposer

### Throughput Materials

#### (Printing and finishing)

- Stock weights: 60 gsm bond to 200 gsm index
- Sizes: 203 mm x 254 mm to 363 mm x 432 mm
- Large format option available for 14.33" x 18.25"
- Lightweight paper option available for 13 lb. bond\*

### Paper Input Capacity

#### (Sheet capacity all at 75 gsm)

- Tray 1: 1,100 sheets; 203 mm x 254 mm to 229 mm x 356 mm
- Tray 2: 600 sheets; 203 mm x 254 mm to 229 mm x 356 mm
- Tray 3: 2,600 sheets of up to 363 mm x 432 mm

### Paper Input Option – Interposers

- 2 Tray Interposer:
  - Tray 4: 550 sheets, non-imageable, of up to 364 mm x 464 mm
  - Tray 5: 2,600 sheets, imageable or non-imageable of up to 364 mm x 464 mm
- 3 Tray Interposer:
  - Tray 4: 550 sheets, non-imageable, of up to 364 mm x 464 mm
  - Tray 5: 550 sheets, imageable or non-imageable of up to 364 mm x 464 mm
  - Tray 6: 550 sheets, imageable or non-imageable of up to 364 mm x 464 mm

### Paper Output Options

- Stacker: 3,000 sheets at 75 gsm  
Optional: 5,000 sheets at 75 gsm (with one High Capacity Stacker)  
Optional: 10,000 sheets at 75 gsm (with two High Capacity Stackers)
- Stitcher: 2 – 70 sheets at 75 gsm  
1 or 2 adjustable stitches.
- Binder: 15 – 125 sheets at 75 gsm  
– Tape colours: Black, blue, red, brown, gray, white or green  
– 425 11" binds per tape reel
- SquareFold Booklet Maker (optional):  
– Fully automatic booklet making system.  
– All operator settings are made with the push of a few buttons.  
– Up to 22 sheets at 20 lb. or 26 sheets at 16 lb.  
– Paper sizes:
 

	Width	Length
Min.	211 mm	279 mm
Max.	297 mm	432 mm
- Cover Insertion Module (CIM) (optional)
- Document Booklet System (DBS) (optional):  
– Adjustable saddle stitch heads, folder, trimmer
- Supports Level 1 Document Finishing Architecture (DFA)

### Client Environments Supported

- Windows 95/98, NT, 2000, XP
- Mac OS 7.6 and above
- Sun OS 4.1.3 / Solaris 1.1.1B
- Solaris 2.3 / 2.4 / 2.5.1 / 2.6 / 8.x

"The bottom line is you can't go wrong with a DocuTech. We give all these models our Editor's Choice rating."

– Better Buys for Business

### PDLs and Data Formats

- Adobe PostScript Level 3/PDF
- PCL 5e • TIFF • ASCII • VIPP Software
- Optional LCDS

### Native Network Environments

- TCP/IP • AppleTalk • Novell (SPX-IPX)

### Electrical Requirements

- Printer Controller: 100/240 VAC + 10%, 47-63 Hz
- Printer Module:
  - 240 VAC, 50 Hz, 30 amp service
  - 200/240 VAC ± 10%, 50 Hz or 3 phase WYE connection, 380 VAC ± 10%, 50 Hz
  - KVA rating: Standby: 2.73; Operating: 6.45 (without Interposer). Standby: 2.80; Operating: 7.65 (with Interposer).
  - Agency certification: UL 1950 IEC 950, CSA 22.2 - 950, FCC (Class A), EN55022 (Class A), CISPR22 (Class A), EN50082-1: 1992 (Generic Immunity Standard), and ICES003 (Class A)
- Interposer (optional): 100/240 VAC + 10%, 47-63 Hz, 10A.

### Physical Characteristics

Width	Depth	Height	Weight
<b>Printer Controller - Processor Module</b>			
254 mm	610 mm	455 mm	32 mm
<b>Printer Controller - Controller Stand</b>			
762 mm	762 mm	965 mm	76.8 kg
<b>Printer Controller - 21" Colour Monitor</b>			
18.1"	16.1"	17.7"	27.7 kg
<b>Printer Module (without optional Interposer)</b>			
3379 mm	1165 mm	1226 mm	1136 kg
<b>Interposer (optional)</b>			
1165 mm	821 mm	1240 mm	322 kg

Please reference the Xerox DigiPath Production Software Specification Sheet for complete DigiPath specifications.



\*Please check with your Fuji Xerox Australia representative for availability.

Fuji Xerox, Xerox, The Document Company and the stylised X are registered trademarks/trademarks. Whilst the information is correct at the time of printing, Fuji Xerox Australia Pty Ltd ABN 63000341819 reserve the right to change the specifications of the equipment described herein without notice. Quality Endorsed Company. ISO 9002. Lic 1950/01 Standards Australia. Printed in Australia, January 2003 • DP6100/6135