IBM

Highlights

- High-performance, dense and energyefficient server ideal for running multiple application and infrastructure workloads in a virtualized environment.
- Consolidation of UNIX and x86 Linux workloads.

IBM Power 730 Express server

A high-performance, reliable and secure infrastructure and application server

Everyone knows what 'performance' meant for IT in the past. Built on the foundation of POWER7® processor technology, our Power Systems Express servers continue to excel and extend industry leadership in the traditional benchmarks of performance.

But, today, the IT landscape is evolving rapidly. And, as processes become more interrelated and complex, IT is being called upon to solve challenging new problems—and implement new IT projects, delivering them with both higher service levels and in a more cost effective manner.

The emerging measures of IT performance today are around agility and the ability to help the business capitalize on new opportunities. IT is measured on providing an infrastructure that can handle rapid growth and manage business risk while meeting higher required service levels. And of course it is expected that new services will be delivered with tighter budget constraints—with IT expected to do more with less and find the lowest cost solutions possible.

Organizations of all sizes are struggling with rising energy prices and limited resources. They are running out of space and exceeding power thresholds in computer rooms and data centers. And, they are increasingly being asked to do more with less. The Power® 730 Express is designed with innovative workload-optimizing and energy management



technologies to help clients get the most out of their systems; that is, running applications fast and energy efficiently to conserve energy and reduce infrastructure costs

The IBM Power 730 Express server delivers the outstanding performance of the POWER7® processor in a dense, rack-optimized form factor and is ideal for running multiple application and infrastructure workloads in a virtualized environment. Take advantage of the Power 730 Express servers' scalability and capacity by leveraging our industrial strength PowerVMTM technology to fully utilize the servers' capability. PowerVM offers this capability to dynamically adjust system resources to partitions based on workload demands, enabling a dynamic infrastructure that can dramatically reduce server sprawl via consolidation of applications and servers.

The Power 730 Express server is a two-socket high-performance, reliable and energy-efficient server supporting up to sixteen POWER7 cores and a choice of AIX®, IBM i or Linux operating systems. Combine the outstanding performance with PowerVM and the workload-optimizing capabilities of POWER7 and you are now ready to run multiple application and infrastructure workloads in a virtualized environment while driving higher utilization and reducing costs.

Power is the performance that delivers business advantage

The leadership performance of the POWER7 processor makes it possible for applications to run faster with fewer processors, resulting in lower per-core software licensing costs. In addition, a single system can now run more applications and reduce the number of required servers lowering infrastructure costs. The new Power 730 Express Model 8231-E2C adds increased memory capacity and high bandwidth Generation 2 PCI-Express slots to provide even greater performance capabilities. And it offers the capability to grow with your business through additional I/O and storage capacities via expansion units.



Power 730 Express rack-mount server

Power is effortlessly balancing workload performance

POWER7 Intelligent Threads technology enables workload optimization by automatically switching between one, two and four execution threads per processor core in order to optimize application throughput. In addition, Active MemoryTM Expansion is a new POWER7 technology, which enables the effective maximum memory capacity to be much larger than the true physical memory without the complexity and cost of installing additional memory devices. These workload-optimizing capabilities can improve application performance and ROI from the server.

Power is dynamic energy optimization

EnergyScale™ Technology offers Intelligent Energy management features, which can dramatically and dynamically conserve power and further improve energy efficiency. These Intelligent Energy features enable the POWER7 processor to operate at a higher frequency if environmental conditions permit, for increased performance and performance per watt; or alternatively operate at a reduced frequency if user settings permit, for significant energy savings. The energy efficiency of the Power 730 is recognized by certain configurations being Energy Star® qualified.

Power is the ability to dynamically allocate resources

Take advantage of the scalability and capacity of the Power 730 Express by leveraging our industrial-strength PowerVM technology to fully utilize the system. PowerVM allows any individual LPAR to access the maximum amount of memory and CPU cores that are available in the server. PowerVM offers this capability to dynamically adjust system resources to partitions based on workload demands, enabling a dynamic infrastructure that dramatically reduces server sprawl via massive consolidation of applications and servers. In addition, optional components in PowerVM Editions are designed to provide advanced virtualization technologies, resulting in efficiencies in resource utilization and cost savings.

Power is availability you can count on

The Power 730 Express is designed with capabilities to deliver leading-edge application availability and allow more work to be processed with less operational disruption. RAS capabilities

include recovery from intermittent errors or failover to redundant components, detection and reporting of failures and impending failures, and self-healing hardware that automatically initiates actions to effect error correction, repair or component replacement. In addition, the Processor Instruction Retry feature provides for the continuous monitoring of processor status with the capability to restart a processor if certain errors are detected. If required, workloads are redirected to alternate processors, all without disruption to application execution.

The Power 730 Express implements Light Path diagnostics, which provide an obvious and intuitive means to positively identify failing components. This allows system engineers and administrators to easily and quickly diagnose hardware problems. Hardware failures that may have taken hours to locate and diagnose can now be detected in minutes, avoiding or significantly reducing costly downtime.

Feature	Benefits
Leadership POWER7 performance	Access data faster and improve response time Do more work with fewer servers and benefit from infrastructure cost savings from a reduction in the number of servers and software licenses
IBM Systems Director Active Energy Manager™ with EnergyScale Technology	Dramatically and dynamically improve energy efficiency and lower energy costs with innovative energy management capabilities Enables businesses to continue operations when energy is limited
PowerVM Virtualization	 Easily add workloads as your business grows Utilize the full capability of the system to reduce infrastructure costs by consolidating workloads running the AIX, IBM i or Linux operating Provides ability to handle unexpected workload peaks by sharing resources
Intelligent Threads	Optimize performance by selecting the suitable threading mode for your application
Active Memory Expansion	Enables more work to be done with existing server resources
RAS Features	Keep applications up and running so you can focus on growing your business
Light Path Diagnostics	Easily and quickly diagnose hardware problems reducing service time.

Power 730 Express at a glance Configuration options			
Sockets	2		
Level 2 (L2) cache	256 KB per core		
Level 3 (L3) cache	4 MB per core		
Memory	8 GB to 256 GB¹ of RDIMM DDR3 Active Memory Expansion		
Solid State Drives (SSD)	Up to 6 SFF drives or		
Disk drives	Up to 6 SFF SAS drives		
Disk capacity	Up to 3.6 TB		
Media bays	Slimline for DVD-RAM Half height for tape drive ² or removable disk		
1/0	Model 8231-E2B	Model 8231-E2C	
PCI Adapter slots	Four PCI Express 8x low profile	Five PCI Express 8x Generation2 low profile	
Standard Ethernet	Four virtual Ethernet 10/100/1000 Mbps ports (or) Two virtual 10 Gigabit Ethernet ports	Two Ethernet 10/100/1000 Mbps ports	
Integrated SAS controller	One controller for SAS DASD/SSD and DVD-RAM Optional protected 175 MB cache with RAID 5, 6	One controller for SAS DASD/SSD with RAID 10, and DVD-RAM Optional protected 175 MB cache with RAID 5, 6	
High performance PCI adapters	8 Gigabit Fibre Channel 10 Gigabit Ethernet 10 Gigabit Fibre Channel over Ethernet	8 Gigabit Fibre Channel Dual port 10 Gigabit Ethernet 10 Gigabit Fibre Channel over Ethernet Dual port QDR Infiniband	
Expansion features (optional)	Storage Expansion up to 102 total SFF bays	Storage Expansion up to 378 total SFF bays Up to 20 PCle slots	

Power 730 Express at a gl	ance		
Other integrated ports	Three USB, two HMC, two system ports, two SPCN		
GX slots	Two GX++		
PowerVM technologies			
POWER Hypervisor™	LPAR, Dynamic LPAR, Virtual LAN (Memory-to-memory interpartition communication)		
PowerVM Express Edition (optional)	Up to three partitions on the server; virtualized disk and optical devices (VIOS); Integrated Virtualization Manage (IVM); Shared Dedicated Capacity		
PowerVM Standard Edition (optional)	PowerVM Express Edition plus Micro-Partitioning™ with up to 10 micropartitions per processor; Multiple Shared Processor Pools		
PowerVM Enterprise Edition (optional)	PowerVM Standard Edition plus Live Partition Mobility (LPM) and Active Memory Sharing (AMS)		
RAS features	ECC memory with Chipkill Processor Instruction Retry Alternate Processor Recovery Service processor with fault monitoring Hot-plug disk bays Hot-plug and redundant power supplies and cooling fans Dynamic component Deallocation		
Operating systems ³	AIX IBM i Linux for POWER®		
High availability	IBM PowerHA™ family		
Power requirements	200 V to 240 V ac, single phase		
System dimensions	Rack Drawer: 3.4 in. H x 17.6 in. W x 28.6 in. D (86 mm x 447 mm x 728 mm); weight 65 lbs (29.5 kg) ⁴		
Warranty (limited)	3 year Limited Warranty, on site for selected components; CRU (customer-replaceable unit) for all other units (varies by country), Next Business Day 9x5 (excluding holidays), warranty service upgrades and maintenance are available		

For more information

To learn more about the IBM Power 730 Express server, please contact your IBM marketing representative or IBM Business Partner, or visit the following websites:

- ibm.com/systems/power/
- http://www-03.ibm.com/systems/power/software/i/
- http://www-03.ibm.com/systems/power/software/aix/
- http://www-03.ibm.com/systems/power/software/
- http://www-03.ibm.com/systems/hardware/energy_star/ index.html

IBM Maintenance and Technical Support solutions can help you get the most out of your IT investment by reducing support costs, increasing availability and simplifying management with integrated support for your multiproduct, multivendor hardware and software environment. For more information on hardware maintenance, software support, solution support and managed support, visit: ibm.com/services/maintenance

Financing solutions from IBM Global Financing can enable effective cash management, protection from technology obsolescence, improved total cost of ownership and return on investment. For more information on IBM Global Financing, visit: ibm.com/financing

All performance information was determined in a controlled environment. Actual results may vary. Performance information is provided "as is" and no warranties or guarantees are expressed or implied by IBM. Buyers should consult other sources of information, including system benchmarks, to evaluate the performance of a system they are considering buying.

When referring to storage capacity, total TB equals total GB divided by 1,000; accessible capacity may be less.

- ¹ 128 GB maximum memory for Power 730 Model 8231-E2B
- ² Tape support results in 3 SFF bays, 1 tape bay and 1 DVD
- ³ See facts and features document for detailed OS level support.
- ⁴ Weight will vary when disks, adapters and peripherals are added.



© Copyright IBM Corporation 2011

IBM Corporation Integrated Marketing Communications Systems and Technology Group Route 100 Somers, NY 10589

Produced in the United States October 2011 All Rights Reserved

This document was developed for products and/or services offered in the United States. IBM may not offer the products, features, or services discussed in this document in other countries.

The information may be subject to change without notice. Consult your local IBM business contact for information on the products, features and services available in your area.

All statements regarding IBM future directions and intent are subject to change or withdrawal without notice and represent goals and objectives only. These are identified by SOD.

IBM, the IBM logo, ibm.com, Power and Power Systems are trademarks or registered trademarks of International Business Machines Corporation in the United States, other countries or both. A full list of U.S. trademarks owned by IBM may be found at: ibm.com/legal/copytrade.shtml

Linux is a trademark of Linus Torvalds in the United States, other countries or both.

UNIX is a registered trademark of The Open Group in the United States, other countries or both.

Other company, product and service names may be trademarks or service marks of others.

IBM hardware products are manufactured from new parts, or new and used parts. In some cases, the hardware product may not be new and may have been previously installed. Regardless, our warranty terms apply.

Photographs show engineering and design models. Changes may be incorporated in production models.

Copying or downloading the images contained in this document is expressly prohibited without the written consent of IBM.

This equipment is subject to FCC rules. It will comply with the appropriate FCC rules before final delivery to the buyer.

Information concerning non-IBM products was obtained from the suppliers of these products or other public sources. Questions on the capabilities of the non-IBM products should be addressed with the suppliers.



Please Recycle

