

Oracle Server X8-2L



x86 SERVERS



KEY FEATURES

- Most flash-dense and energy-efficient 2U enterprise-class server
- Highest levels of security enabled out of the box
- Two Intel® Xeon® Scalable Processor Second Generation CPUs
- Twenty-four DIMM slots with maximum memory of 1.5 TB
- Eleven PCIe Gen 3 slots
- Up to 168 TB SAS-3 disk storage in 12 slots in standard configurations
- Up to 102.4 TB NVMe Express high-bandwidth flash storage in the all-flash configuration
- Hot-swappable and redundant disks, cooling fans, and power supply units
- Oracle ILOM

Oracle Server X8-2L is the ideal 2U platform for databases, enterprise storage, and big data solutions. Supporting the standard and enterprise editions of Oracle Database, this server delivers best-in-class database reliability in single-node configurations. With support for up to 102.4 TB of high-bandwidth NVMe Express (NVMe) flash storage, Oracle Database using its Database Smart Flash Cache feature, as well as NoSQL and Hadoop applications, can be significantly accelerated. Optimized for compute, memory, I/O, and storage density simultaneously, Oracle Server X8-2L delivers extreme storage capacity at lower cost when combined with Oracle Solaris and ZFS file system compression. Each server comes with built-in, proactive fault detection and advanced diagnostics, along with firmware that is already optimized for Oracle software, to deliver extreme reliability.

Product Overview

Oracle Server X8-2L is designed and built specifically for the demands of enterprise workloads. It is a crucial building block in Oracle engineered systems and Oracle Cloud Infrastructure. Powered by two Platinum, or Gold Intel® Xeon® Scalable Processor Second Generation CPUs with up to 24 cores per socket, along with 24 memory slots, this server offers high-performance processors plus the most dense flash storage options in a 2U enclosure. Oracle Server X8-2L is the most balanced and highest performing 2U enterprise server in its class because it offers optimal core and memory density combined with high I/O throughput.

In addition to optimized processing power and storage density, Oracle Server X8-2L offers 11 PCIe 3.0 expansion slots (one 16-lane and ten 8-lane) for maximal I/O card and port density. With 192 gigabytes per second of bidirectional I/O bandwidth, Oracle Server X8-2L can handle the most demanding enterprise workloads.

Oracle Server X8-2L offers best-in-class reliability, serviceability, and availability (RAS) features that increase overall uptime of the server. This extreme reliability makes Oracle Server X8-2L the best choice for single-node Oracle Database deployments in remote or branch office locations. Real-time monitoring of the health of the CPU, memory, and I/O subsystems, coupled with offlining capability of failed components, increases the system availability. Building on the firmware-level problem detection, Oracle Linux and Oracle Solaris are enhanced to provide fault detection capabilities when running on Oracle Server X8-2L. In addition, exhaustive system diagnostics and hardware-assisted error reporting and logging enable identification of failed components for ease of service.



KEY BENEFITS

- Reduce vulnerability to cyberattacks
- Accelerate Oracle Database, NoSQL, and Hadoop applications using Oracle's unique NVM Express design
- Satisfy demands of enterprise applications with extreme I/O card density
- Increase uptime with built-in diagnostics and fault detection from Oracle Linux and Oracle Solaris
- Increase storage capacity 15x, combining extreme compute power with Oracle Solaris and ZFS compression
- Maximize system power efficiency with Oracle Advanced System Cooling
- Maximize IT productivity by running Oracle software on Oracle hardware

To help users achieve accelerated performance of Oracle Database, Oracle Server X8-2L supports hot-swappable, high-bandwidth flash that combines with Database Smart Flash Cache to drive down cost per database transaction. In the all-flash configuration, with Oracle's unique NVM Express design, Oracle Server X8-2L supports up to 12 small form factor NVMe drives and up to four NVMe add-in cards, for a total capacity of 102.4 TB. This massive flash capacity also benefits NoSQL and Hadoop applications, reducing network infrastructure needs and accelerating performance with 25 GB per second of total NVMe bidirectional bandwidth.

For maximizing storage capacity, Oracle Server X8-2L is also offered in a standard 12-disk configuration, with 3.5-inch large form factor disk slots accommodating high-capacity hard disk drives (HDDs). A maximum 168 TB of direct-attached storage makes Oracle Server X8-2L ideally suited as a storage server. The compute power of this server can be used to extend storage density even further with Oracle Solaris and ZFS file system compression to achieve up to 15x compression of data without significant performance impact. Oracle Server X8-2L is also well suited for other storage-dense implementations, such as video compression and transcoding, which require a balanced combination of compute power and storage capacity at the same time.

Oracle Server X8-2L ships with Oracle ILOM 4.0, a cloud-ready service processor designed for today's security challenges. Oracle ILOM provides real-time monitoring and management of all system and chassis functions as well as enables remote management of Oracle servers. Oracle ILOM uses advanced service processor hardware with built-in hardening and encryption as well as improved interfaces to reduce the attack surface and improve overall security. Oracle ILOM has improved firmware image validation through the use of improved firmware image signing. This mechanism provides silicon-anchored service processor firmware validation that cryptographically prevents malicious firmware from booting. After Oracle ILOM's boot code is validated by the hardware, a chain of trust allows each subsequent firmware component in the boot process to be validated. Finally, with a focus on security assurance, using secure coding and testing methodologies, Oracle is able to maximize firmware security by working to prevent and remediate vulnerabilities prior to release.

With advanced system cooling that is unique to Oracle, Oracle Server X8-2L achieves system efficiencies that result in power savings and maximum uptime. Oracle Advanced System Cooling utilizes remote temperature sensors for fan speed control, minimizing power consumption while keeping optimal temperatures inside the server. These remote temperature sensors are designed into key areas of this server to ensure efficient fan usage by organizing all major subsystems into cooling zones. This technology helps reduce energy consumption in a way that other servers cannot.

Oracle Premier Support customers have access to My Oracle Support and multiserver management tools in Oracle Enterprise Manager 13c. Oracle Enterprise Manager 13c, a critical component that enables application-to-disk system management, coordinates servers, storage, and networking for a complete cloud infrastructure as a service (IaaS). Oracle Enterprise Manager 13c also features an automated service request capability, whereby potential issues are detected and reported to Oracle's support center without user intervention, assuring the maximum service levels and simplified support.

With industry-leading in-depth security spanning its entire portfolio of software and systems, Oracle believes that security *must* be built in at every layer of the IT

Oracle Server X8-2L is the most storage-dense, versatile two-socket server for the enterprise data center, packing the optimal balance of compute power, memory capacity, and I/O capacity into a compact and energy-efficient 2U enclosure.

RELATED PRODUCTS

- Oracle Server X8-2
- Oracle Server X8-8

RELATED SERVICES

The following services are available from Oracle Customer Support:

- Support
- Installation
- Eco-optimization services

environment. In order to build x86 servers with end-to-end security, Oracle maintains 100 percent in-house design, controls 100 percent of the supply chain, and controls 100 percent of the firmware source code. Oracle's x86 servers enable only secure protocols out of the box to prevent unauthorized access at point of install. For even greater security, customers running Oracle Ksplice on Oracle's x86 servers will benefit greatly from zero downtime patching of the Oracle Linux kernel.

Oracle is driven to produce the most reliable and highest performing x86 systems, with security-in-depth features layered into these servers, for two reasons: Oracle Cloud Infrastructure and Oracle Engineered Systems. At their foundation, these rapidly expanding cloud and converged infrastructure businesses run on Oracle's x86 servers. To ensure that Oracle's SaaS, PaaS, and IaaS offerings operate at the highest levels of efficiency, only enterprise-class features are designed into these systems, along with significant co-development among cloud, hardware, and software engineering. Judicious component selection, extensive integration, and robust real-world testing enable the optimal performance and reliability critical to these core businesses. All the same features and benefits available in Oracle's cloud are standard in Oracle's x86 standalone servers, helping customers to easily transition from on-premises applications to cloud with guaranteed compatibility and efficiency.

Oracle Server X8-2L System Specifications

ARCHITECTURE

Processor

- One or two processors from the Intel® Xeon® Scalable Processor Second Generation CPUs (two processors required for maximum memory and I/O configurations)
- Up to 24 cores per processor
- Intel® Xeon® Platinum 8268 processor: 2.9 GHz, 24 cores, 205 watts, XCC, 35.75 MB L3 cache
- Intel® Xeon® Platinum 8260 processor: 2.4 GHz, 24 cores, 165 watts, XCC, 35.75 MB L3 cache
- Intel® Xeon® Gold 5218 processor: 2.3 GHz, 16 cores, 125 watts, XCC, 22 MB L3 cache
- Intel® Xeon® Gold 5222 processor: 3.8 GHz, 4 cores, 105 watts, XCC, 16.50 MB L3 cache

Cache

- Level 1: 32 KB instruction and 32 KB data L1 cache per core
- Level 2: 1 MB shared data and instruction L2 cache per core
- Level 3: up to 1.375 MB shared inclusive L3 cache per core

Main Memory

- Twenty-four DIMM slots provide up to 1.5 TB of DDR4 DIMM memory
- RDIMM options: 16 GB at DDR4-2666 single rank and 32 GB at DDR4-2666 dual rank
- LRDIMM option: 64 GB at DDR4-2666 dual rank

INTERFACES

Standard I/O

- One 1 Gb Ethernet port and one serial RJ-45 port
- Two USB 3.0 ports (one rear, one internal)
- Expansion bus: 11 PCIe 3.0 slots, 1 x16 and 10 x8 slots
- Supports LP-PCIe cards including Ethernet, InfiniBand, FC, SAS HBAs, and flash

Storage

- Twelve 3.5-inch front hot-swappable disk bays plus two internal M.2 boot drives
- Disk bays can be populated with 3.5-inch 14 TB HDDs or 2.5-inch NVMe solid-state drives (SSDs)
- PCIe flash
- Sixteen-port 12 Gb/sec RAID HBA supporting levels: 0, 1, 5, 6, 10, 50, and 60 with 1 GB of DDR3 onboard memory with flash memory backup via embedded internal SAS-3 HBA PCIe card

- Eight-port 12 Gb/sec SAS HBA with direct access to up to eight internal SAS-3 HDDs (two per system required)

High-Bandwidth Flash

- All flash configuration—up to 102.4 TB in the all-flash configuration (maximum of 12 hot-swappable 6.4 TB NVMe SSDs and four 6.4 TB NVMe PCIe cards)
 - » NVMe functionality in 3.5-inch disk bays requires an Oracle NVMe enabling kit that consumes one PCIe slot for every three NVMe devices (maximum of four kits)
- Standard configuration: up to 51.2 TB in the standard configuration (maximum of eight 6.4 TB NVMe PCIe cards)

SYSTEMS MANAGEMENT

Interfaces

- Dedicated 10/100/1000 Base-T network management port
- In-band, out-of-band, and side-band network management access
- RJ-45 serial management port

Service Processor

Oracle Integrated Lights Out Manager (Oracle ILOM) provides:

- Remote keyboard, video, and mouse redirection
- Full remote management through command-line, IPMI, and browser interfaces
- Remote media capability (USB, DVD, CD, and ISO image)
- Advanced power management and monitoring
- Active Directory, LDAP, and RADIUS support
- Dual Oracle ILOM flash
- Direct virtual media redirection
- FIPS 140-2 mode using OpenSSL FIPS certification (#1747)

Monitoring

- Comprehensive fault detection and notification
- In-band, out-of-band, and side-band SNMP monitoring v2c and v3
- Syslog and SMTP alerts
- Automatic creation of a service request for key hardware faults with Oracle automated service request (ASR)

Oracle Enterprise Manager

- Deployment and provisioning of server bare metal
- Cloud and virtualization management
- Inventory control and patch management
- OS observability for performance monitoring and tuning
- Automated service request (ASR) generation
- Single pane of glass for management of all Oracle deployment whether on premises or in Oracle Cloud

SOFTWARE

OPERATING SYSTEMS

- Oracle Linux
- Oracle Solaris

For more information on software go to: [Oracle Server X8-2L Options & Downloads](#)

VIRTUALIZATION

- Oracle VM

For more information on software go to: [Oracle Server X8-2L Options & Downloads](#)

ENVIRONMENT

- Operating temperature: 5°C to 35°C (41°F to 95°F)
- Nonoperating temperature: -40°C to 70°C (-40°F to 158°F)
- Operating relative humidity: 10% to 90%, noncondensing
- Nonoperating relative humidity: up to 93%, noncondensing
- Operating altitude: up to 9,840 feet (3,000 m*) maximum ambient temperature is derated by 1°C per

300 m above 900 m (*except in China where regulations may limit installations to a maximum altitude of 6,560 feet or 2,000 m)

- Nonoperating altitude: up to 39,370 feet (12,000 m)
 - Acoustic noise: 8.1 Bels A-weighted operating, 5.8 Bels A-weighted idling
-

POWER

- Two 1,200 watt hot-swappable and redundant power supplies, rated 96% efficiency
- Rated line voltage: 100 to 240 VAC
- Rated input current 100 to 127 VAC 7.2 A and 200 to 240 VAC 3.4 A

For more information on power consumption, go to: [Oracle Server X8-2L Power Calculator](#)

REGULATIONS

- Product safety: UL/CSA-60950-1, EN60950-1-2006, IEC60950-1 CB scheme with all country differences
 - EMC
 - Emissions: FCC CFR 47 Part 15, ICES-003, EN55022, EN55032, KN32, EN61000-3-2, and EN61000-3-3
 - Immunity: EN55024, KN35
-

CERTIFICATIONS¹

- North America Safety (NRTL)
 - European Union (EU)
 - International CB Scheme
 - BIS (India)
 - BSMI (Taiwan)
 - RCM (Australia)
 - CCC (PRC)
 - MSIP (Korea)
 - VCCI (Japan)
 - Morocco
 - Republic of Srpska
-

EUROPEAN UNION DIRECTIVES

- 2014/35/EU Low Voltage Directive
 - 2014/30/EU EMC Directive
 - 2011/65/EU RoHS Directive
 - 2012/19/EU WEEE Directive
-

DIMENSIONS AND WEIGHT

- Height: 86.9 mm (3.4 in.)
 - Width: 445.0 mm (17.5 in.)
 - Depth: 759.4 mm (29.9 in.)
 - Weight: 28.6 kg (63 lb.) fully populated
-

INCLUDED INSTALLATION KITS

- Tool-less rackmounting slide rail kit
 - Cable management arm
-


¹ All standards and certifications referenced are to the latest official version. For additional detail, please contact your sales representative. Other country regulations/certifications may apply.



CONTACT US

For more information about Oracle Server X8-2L, visit oracle.com or call +1.800.ORACLE1 to speak to an Oracle representative.

CONNECT WITH US



Integrated Cloud Applications & Platform Services

Copyright © 2019, Oracle and/or its affiliates. All rights reserved. This document is provided for information purposes only, and the contents hereof are subject to change without notice. This document is not warranted to be error-free, nor subject to any other warranties or conditions, whether expressed orally or implied in law, including implied warranties and conditions of merchantability or fitness for a particular purpose. We specifically disclaim any liability with respect to this document, and no contractual obligations are formed either directly or indirectly by this document. This document may not be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose, without our prior written permission.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group. 0319



Oracle is committed to developing practices and products that help protect the environment